



Sr No	PART	MATERIAL	QTY
1	END CONNECTOR	ASTM A479 Gr. SS316L	1
2	BODY	ASTM A479 Gr. SS316L	1
3	PRIMARY SEAL	PTFE	1
4	SECONDARY SEAL	GRAPHITE	1
5	CONN. O RING	VITON (AED TYPE)	1
6	BALL	ASTM A479 Gr. SS316L	1
7	BALL SEAT	PEEK	2
8	THRUST SEAL	CFT	1
9	SPINDLE O-RING	VITON (AED TYPE)	1
10	GLAND SEAL	CFT	1
11	GLAND WASHER	ASTM A479 Gr. SS316L	1
12	LOCK PIN	SS 304	1
13	SPINDLE	ASTM A479 Gr. SS316L	1
14	HANDLE NUT	SS304	1
15	ALLEN BOLT	SS304	1
16	HANDLE	SS304	1
17	HANDLE SLEEVE	PVC	1

SPECIFICATION:

1/4" Turn Lever Type Operation
 Max Pressure Rating: 6000 psig @ 100 °F

End Connection: 1/2" BSPP-F
 Bore Diameter: Ø10.0 mm

Testing : As per API 598
 Body Test Press (Hydro): 15000 psig
 Seat Test Press (Hydro): 9000 psig
 Seat Test Press (Pneu): 90 psig
 Nace MR0175 Applicable

havi
 Fittings & Valves
 info@havi.in www.havi.in
 A-201, PRIME TRADE CENTER
 SATIVALI ROAD, VASAI (E),
 PALGHAR - 401208, MAHARASHTRA, INDIA

	SIGN	DATE
DRAWN BY	VK	22.12.2022
CHECKED BY	RW	22.12.2022
APPROVED BY	AS	22.12.2022

PART NAME : BALL VALVE 6K SERIES 1/2" BSPP(F) X 1/2" BSPP(F)		CUSTOMER NAME:	
DWG NO : BV10K-10B-8IPF-8IPF-S6L		PROJECT NAME & NO:	
MATERIAL : - AS PER BOM		ENQ NO: EN2223/01069	
REV NO		SIGN	
DESCRIPTION		DATE	
SO NO:		SHEET NO: 01 OF 01	
* All dimensions are in mm. Dimensions for reference only and are subject to change without notice		REV NO: 00	
* This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI.		SCALE: NTS	

PATH: X:\2022-2023\EXPORT\EN222301069\GAD