



Sr No	PART	MATERIAL	QTY
1	END CONNECTOR	ASTM A479 Gr. SS316L	1
2	BODY	ASTM A479 Gr. SS316L	1
3	PRIMARY SEAL	PTFE	1
4	SECONDARY SEAL	GRAPHITE	1
5	CONN. O RING	VITON (AED TYPE)	1
6	BALL	ASTM A479 Gr. SS316L	1
7	BALL SEAT	PEEK	2
8	THRUST SEAL	CFT	1
9	SPINDLE O-RING	VITON (AED TYPE)	1
10	GLAND SEAL	GRAPHITE	1
11	GLAND WASHER	ASTM A479 Gr. SS316L	1
12	LOCK PIN	SS 304	1
13	SPINDLE	ASTM A479 Gr. SS316L	1
14	HANDLE NUT	SS304	1
15	ALLEN BOLT	SS304	1
16	HANDLE	SS304	1
17	HANDLE SLEEVE	PVC	1

SPECIFICATION:

1/4" Turn Lever Type Operation
 Max Pressure Rating: 6000 psig @ 100 °F

Process Connection: 1/2" NPT-M (ASME B1.20.1)
 Instrument Connection: 1/2" NPT-F (ASME B1.20.1)
 Bore Diameter: Ø10.0 mm

Testing : As per API 598
 Body Test Press (Hydro): 9000 psig
 Seat Test Press (Hydro): 6600 psig
 Seat Test Press (Pneu): 90 psig



PART NAME :
 BALL VALVE 6K SERIES 1/2" NPT(M) X 1/2" NPT(F)

DWG NO : - BV6K-10B-8M-8F-S6L
 MATERIAL : - AS PER BOM

CUSTOMER NAME:
 -

PROJECT NAME & NO:
 -

ENQ NO: EN2223/00036

SO NO: -

	SIGN	DATE
DRAWN BY	VK	04.05.2022
CHECKED BY	RW	04.05.2022
APPROVED BY	SM	04.05.2022

REV NO	DESCRIPTION	SIGN	DATE

* All dimensions are in mm. Dimensions for reference only and are subject to change without notice
 * This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI.



SHEET NO:
 01 OF 01

REV NO: 00

SCALE: NTS