



Sr No	PART	DRAWING NO.	QTY
1	END CONNECTOR	ASTM A479 Gr. SS 316	1
2	BODY	ASTM A479 Gr. SS 316	1
3	PRIMARY SEAL	PTFE	1
4	SECONDARY SEAL	GRAPHITE	1
5	CONNECTOR O-RING	VITON (AED TYPE)	1
6	BALL	ASTM A479 Gr. SS 316	1
7	BALL SEAT	RPTFE	2
8	THRUST SEAL	CARBON FILLED PTFE	1
9	SPINDLE O-RING	VITON (AED TYPE)	1
10	GLAND SEAL	CARBON FILLED PTFE	1
11	GLAND WASHER	ASTM A479 Gr. SS 316	1
12	LOCK PIN	SS304	1
13	STEM	ASTM A479 Gr. SS 316	1
14	HANDLE NUT	SS 304	1
15	ALLEN BOLT	SS 304	1
16	HANDLE	SS 304	1
17	HANDLE SLEEVE	PVC	1

SPECIFICATION:

Inlet Conn.: 1-1/2" BSPP-F
 Outlet Conn.: 1-1/2" BSPP-F
 Max Pressure Rating: 6000 psig @ 38 °C

Bore Ø : 25MM

Testing : As per API 598
 Body Test Press (Hydro): 9000 psig
 Seat Test Press (Hydro): 6600 psig
 Seat Test Press (Pneu): 90 psig

Material: AS PER BOM



PART NAME : BALL VALVE, 25MM BORE (6000 PSIG)
 1-1/2" BSPP-F X 1-1/2" BSPP-F

DWG NO.: BV6K-25B-24IPF-24IPF-S6

MATERIAL: AS PER BOM

CUSTOMER NAME:

PROJECT NAME:

SO NO: -

ENQ NO: EN2223/01400



SHEET NO.:
01/01

	SIGN	DATE
DRAWN BY	SP	08.03.2023
CHECKED BY	MT	08.03.2023
APPROVED BY	SRD	08.03.2023

REV NO	DESCRIPTION	SIGN	DATE

* All dimensions are in mm. Dimensions for reference only and are subject to change without notice
 * This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI.

REV NO: 00

SCALE: NTS

PATH: C:\USERS\DESIGN\3\DESKTOP\SAGAREN\EN2223-01400