



SR NO	DESCRIPTION	QTY	MATERIAL
1	BODY	1	SS 316
2	NUT	1	SS 316
3	FRONT FERRULE	1	SS 316
4	BACK FERRULE	1	SS 316

SR NO	PART NO	ØT	Tx	L	F (A/F)	G (A/F)	ØE	Pressure Rating (Psig)	Temperature Range
12	3MMC2N-S6-N	3mm	1/8" NPT-M	32.0	11.0	11.0	2.4	6000 Psig	-192°C to 649°C
11	6MMC2N-S6-N	6mm	1/8" NPT-M	33.5	14.0	14.0	4.2	6000 Psig	-192°C to 649°C
10	6MMC4N-S6-N	6mm	1/4" NPT-M	38.3	14.0	14.0	4.2	6000 Psig	-192°C to 649°C
14	6MMC8IT-S6-N	6mm	1/2" BSPT-M	44.6	22.0	14.0	4.2	6000 Psig	-192°C to 649°C
9	10MMC4N-S6-N	10mm	1/4" NPT-M	40.0	17.5	19.0	7.9	6000 Psig	-192°C to 649°C
3 & 15	10MMC8IT-S6-N	10mm	1/2" BSPT-M	46.0	22.0	19.0	7.9	6000 Psig	-192°C to 649°C
2	14MMC8IT-S6-N	14mm	1/2" BSPT-M	49.7	25.0	25.0	11.7	3000 Psig	-192°C to 649°C
5	18MMC8N-S6	18mm	1/2" NPT-M	51.3	27.0	32.0	11.8	3000 Psig	-192°C to 649°C

PART NAME : MALE CONNECTOR - TUBE OD x Male Threading				CUSTOMER NAME:-			
DWG NO : GA-MC-S6-N				PROJECT NAME:-			
MATERIAL : AS PER BOM				PO NO:-			
DRAWN BY : VK				ENQ NO: EN2223/01201			
CHECKED BY : SB				SHEET NO: 01 OF 01			
APPROVED BY : SD				SO NO: -			
REV NO	DESCRIPTION	SIGN	DATE				
				* All dimensions are in mm. Dimensions for reference only and are subject to change without notice * This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI.			
				REV NO: 00			
				SCALE: NTS			

NOTE:  
• # MARKED DIMENSION IS IN FINGER TIGHT POSITION.

J  
I  
H  
G  
F  
E  
D  
C  
B  
A

PATH - X:\2022-2023\EXPORT\EN222301201\GAD