



SR NO	PART NO	Tx	Gx	L	H (A/F)	ØE	QTY
29	4NHRN2N-S6	1/4" NPT (M)	1/8" NPT (M)	31.0	14(9/16")	4.7	11
30	12NHRN8N-S6	3/4" NPT (M)	1/2" NPT (M)	46.2	27(1-1/16")	11.9	11
31	16NHRN8N-S6	1" NPT (M)	1/2" NPT (M)	53.1	36(1-7/16")	11.8	11

NOTES:-

- 1) ALL DIMENSIONS ARE IN MM UNLESS AND OTHERWISE SPECIFIED.
- 2) # MARKED DIMENSIONS ARE IN FINGER TIGHT POSITION.
- 3) THREAD CONNECTIONS AS PER ANSI/ASME B1.20.1 (NPT)
- 4) TEMPERATURE RANGE - -192°C TO 649°C.
- 5) MWP.: 3000 PSIG @ 100 °F

PART NAME : HEX REDUCING NIPPLE NPT(M) x NPT(M)				CUSTOMER NAME:-			
DWG NO : NHN-S6				PROJECT NAME:-			
MATERIAL : SS 316				PO NO:- VSP-14041794			
				ENQ NO: EN2223/01219			
				SO NO:- SO2324/00159			
				SHEET NO: 15 OF 20			
				REV NO: 00			
				SCALE: NTS			

	SIGN	DATE
DRAWN BY	PDG	22-08-2023
CHECKED BY	VSM	22-08-2023
APPROVED BY	SRD	22-08-2023



www.havi.in
info@havi.in

* All dimensions are in mm. Dimensions for reference only and are subject to change without notice
* This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI.