



Sr No	PART	MATERIAL	QTY
1	BODY	ASTM A479 Gr. SS316	1
2	END CONNECTOR	ASTM A479 Gr. SS316	1
3	CONNECTOR PACKING	PTFE	1
4	BALL SEAT	PTFE/RPTFE	2
5	BALL	ASTM A479 Gr. SS316	1
6	STEM SEAL	PTFE	2
7	SPACER	ASTM A479 Gr. SS316	1
8	HANDLE NUT	SS304	1
9	DOWEL PIN	SS304	1
10	STEM	ASTM A479 Gr. SS316	1
11	HANDLE	SS304	1
12	HANDLE SLEEVE	PVC	1

Data Sheet.

Process Conn.: 1/2" NPT(F)
 Instrument Conn.: 1/2" NPT(F)
 Bore.: Ø9.5mm

M W P.: 1500psig @ 100 °F
 Seat Test Press (Hydro): 1650 psig
 Seat Test Press (Pneu): 90 psig
 Body Test Press (Hydro): 2250 psig

NOTE :- UNLESS SPECIFIED ALL DIMENSIONS ARE IN 'mm'

 Fittings & Valves info@havi.in www.havi.in A-201, PRIME TRADE CENTER SATIVALI ROAD, VASAI (E), PALGHAR - 401208, MAHARASHTRA, INDIA	PART NAME : LOW PRESSURE BALL VALVE 1/2" NPTF X 1/2" NPTF				CUSTOMER NAME :-VSP				
	DWG NO : - LBV-8F-8F-S6				END USER NAME :-				
	MATERIAL :- AS PER BOM				PROJECT NAME :-				
					ENQ NO - EN2324/00672				
				SO NO :-SO2324/0441				 SHEET NO: 01 OF 01	
DRAWN BY		ASN	13.03.2024		* All dimensions are in mm. Dimensions for reference only and are subject to change without notice * This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI.				REV NO: 00
CHECKED BY		SRD	13.03.2024						SCALE: NTS
APPROVED BY		SRD	13.03.2024						

PATH:-X:\FY 2023-24\ISO-0441