



SR.	DESCRIPTION	MATERIAL	QTY
1	Handle	SS 304	1
2	Body	ASTM A479 Gr.SS316	1
3	Pusher	ASTM A479 Gr.SS316	1
4	Packing	PTFE	1
5	Spindle	ASTM A479 Gr.SS316	1
6	Seal Ring	PTFE	2
7	Ball	ASTM A479 Gr.SS316	1
8	End Connector	ASTM A479 Gr.SS316	2
9	Seat	PTFE	2
10	Thrust Washer	PTFE	1
11	Panel Nut	SS316	1
12	Locker	SS316	1
13	Handle Nut	SS316	1

DATA SHEET

Type : 3 Way 'L' Port
 Connection : 1/2" NPT(F)
 Orifice: 10.3mm

Working Press : 1500 psig
 Seat Test (Hydro) : 1650 psig
 Body Test (Hydro) : 2250 psig
 Pneumatic Seat Test : 90 psig

 Fittings & Valves info@havi.in www.havi.in A-201, PRIME TRADE CENTER SATIVALI ROAD, VASAI (E), PALGHAR - 401208, MAHARASHTRA, INDIA	PART NAME : Low Pressure Ball Valve 3 way, 1/2" NPT-F				CUSTOMER NAME : -			
	DWG NO : - LBV-8F3W-S6				PROJECT NAME & NO :			
	MATERIAL : - AS PER BOM				ENQ NO:- 2324/00253			
					SO NO: SO2122/00026			
	SIGN	DATE	REV NO	DESCRIPTION	SIGN	DATE	 SHEET NO: 01 OF 01	
DRAWN BY	MBC	08.06.2023					REV NO: 00	
CHECKED BY	MST	08.06.2023					SCALE: NTS	
APPROVED BY	SRD	08.06.2023	* All dimensions are in mm. Dimensions for reference only and are subject to change without notice * This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI.					

PATH: C:\USERS\DESIGNER\DESKTOP\ENQUIRY\EN2324\00253