

SR.	DESCRIPTION	MATERIAL	QTY
1	HANDLE	SS 304	1
2	BODY	ASTM A479 Gr.316	1
3	PUSHER	ASTM A479 Gr.316	1
4	PACKING	PTFE	1
5	SPINDLE	ASTM A479 Gr.316	1
6	SEAL RING	PTFE	2
7	BALL	ASTM A479 Gr.316	1
8	END CONNECTOR	ASTM A479 Gr.316	2
9	SEAT	PTFE	2
10	THRUST WASHER	PTFE	1
11	PANEL NUT	SS316	1
12	LOCKER	SS316	1
13	HANDLE NUT	SS316	1



DATA SHEET

Type : 3 Way 'L' Port
 Connection : 1/2" BSPT(F)
 Orifice: 10.3mm

M.W.T:- -54°C To 260°C
 Working Pre. : 3000 psi
 Seat Test (Hydro) : 3300 psi
 Body Test (Hydro) : 4500 psi
 Pneumatic Seat Test : 90 psi



PART NAME :
 Low Pressure Ball Valve 3 way, 1/2" BSPT-F 3000 Psig


DWG NO : - LBV-8ITF3W-S6-3K
 MATERIAL : - AS PER BOM

CUSTOMER NAME:
 -

PROJECT NAME & NO:

ENQ NO: 2324/00424

SO NO: NA



SHEET NO:
 01 OF 01

	SIGN	DATE
DRAWN BY	MBC	17.07.2023
CHECKED BY	VM	17.07.2023
APPROVED BY	SRD	17.07.2023

* All dimensions are in mm. Dimensions for reference only and are subject to change without notice
 * This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI.

REV NO: 00
 SCALE: NTS

PATH: X:\2023-2024\EXPORT\232400424\GAD 232400424\R1-21.07.2023