



Sr No	PART	MATERIAL	QTY
1	BODY	ASTM A479 Gr. SS316L	1
2	END CONNECTOR	ASTM A479 Gr. SS316L	1
3	CONNECTOR PACKING	CFT	1
4	BALL SEAT	PCTFE	2
5	BALL	ASTM A479 Gr. SS316L	1
6	STEM SEAL	CFT	2
7	SPACER	ASTM A479 Gr. SS316L	1
8	HANDLE NUT	ASTM A479 Gr. SS316	1
9	DOWEL PIN	SS304	1
10	STEM	ASTM A479 Gr. SS316L	1
11	HANDLE	SS304	1
12	HANDLE SLEEVE	PVC	1

Data Sheet.
 Process Conn.: 1/2" NPT(M)
 Instrument Conn.: 1/2" NPT(F)
 Bore.: Ø9.5mm

M W P.: 1000psig
 Seat Test Press (Hydro): 1100 psig
 Seat Test Press (Pneu): 90 psig
 Body Test Press (Hydro): 1500 psig
 Temp. Range: -60 to 130°C

	SIGN	DATE
DRAWN BY	SDB	18.08.2022
CHECKED BY	JVK	18.08.2022
APPROVED BY	SM	18.08.2022

havi
 Fittings & Valves
 www.havi.in
 info@havi.in

PART NAME : Low Temperature & Pressure Ball Valve 1/2" NPT(M) x 1/2" NPT(F)		CUSTOMER NAME :	
PART NO : LTBV-8M-8F-S6L-N		PROJECT NAME : ---	
MATERIAL : AS PER BOM		END USER NAME : ---	
REV NO	DESCRIPTION	SIGN	DATE
SO NO:		ENQ NO: EN2223/00343	
* All dimensions are in mm. Dimensions for reference only and are subject to change without notice		SHEET NO: 01 OF 01	
* This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI.		REV NO: 00	
		SCALE: NTS	

NOTE:- UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN 'mm'

PATH: Z:\2022-2023\EXPORT\EN222300536\R1\IGAD