


SR.	DESCRIPTION	MATERIAL	QTY
1	HANDLE	NYLON 6	1
2	GRUB SCREW	SS316	1
3	SPINDLE	ASTM A479 Gr.SS316	1
4	PUSHER	SS316	1
5	LOCK NUT	SS316	1
6	PACKING	PTFE	2
7	END CONNECTOR	ASTM A479 Gr.SS316	2
8	CONNECTOR PACKING	PTFE	2
9	BALL SEAT	PEEK	2
10	BODY	ASTM A479 Gr.SS316	1
11	BALL	ASTM A479 Gr.SS316	1

DATA SHEET

Type : 2 Way, Full Port
 Inlet Connection : 3/4" NPT(F)
 Outlet Connection : 3/4" NPT(F)
 Orifice: 10.3mm

Working Press : 6000 psi
 Seat Test (Hydro) : 6600 psi
 Body Test (Hydro) : 9000 psi
 Pneumatic Seat Test : 90 psi

 Fittings & Valves info@havi.in www.havi.in A-201, PRIME TRADE CENTER SATIVALI ROAD, VASAI (E), PALGHAR - 401208, MAHARASHTRA, INDIA	PART NAME : Medium Pressure Panel Mounted Ball Valve, 3/4" NPT-F & 3/4" NPT-F				CUSTOMER NAME :				
	DWG NO : - MBV-12F-12F-S6				PROJECT NAME :				
	MATERIAL : - AS PER BOM				ENQ NO: EN2324/00354				
					SO NO:				
SIGN		DATE		SIGN		DATE		SHEET NO: 01 OF 01	
DRAWN BY		MBC		04.07.2023				REV NO: 00	
CHECKED BY		MV		04.07.2023				SCALE: NTS	
APPROVED BY		SD		04.07.2023					
* All dimensions are in mm. Dimensions for reference only and are subject to change without notice * This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI.									

PATH: -W\2023-2024\EXPORT\EN232400354\GAD