

Sr No	Description	Material	Qty
1	Nut	SS 316	2
2	Back Ferrule	SS 316	2
3	Front Ferrule	SS 316	2
4	Side Connector	ASTM A479 Gr. SS316	2
5	Connector Packing	PTFE	2
6	Body	ASTM A479 Gr. SS316	1
7	Ball	ASTM A479 Gr. SS316	1
8	Seat	PCTFE	2
9	Stem Seal	PTFE	2
10	Spindle	ASTM A479 Gr. SS316	1
11	Check Nut	SS 316	1
12	Pusher	ASTM A479 Gr. SS316	1
13	Grub Screw	SS 316	2
14	Handle	NYLON 6	1


Data Sheet.

Process Conn.: 12mm ODT
 Instrument Conn.: 12mm ODT
 Bore.: Ø10.3mm

M W P.: 6000psig @ 100 °F
 Seat Test Press (Hydro): 6600 psig
 Seat Test Press (Pneu): 90 psig
 Body Test Press (Hydro): 9000 psig

Materials.: AS PER BOM

Temperature Range of Valve is -60° to 200°C

 Fittings & Valves info@havi.in www.havi.in A-201, PRIME TRADE CENTER SATIVALI ROAD, VASAI (E), PALGHAR - 401208, MAHARASHTRA, INDIA			PART NAME : Medium Pressure Panel Mounting Ball Valve, 12mm ODT X 12mm ODT with PCTFE Seat		CUSTOMER NAME:		
			DWG NO : MBV-12MT-12MT-S6-PCTFE		PROJECT NAME & NO:		ENQ NO: EN222300744
DRAWN BY		SIGN		DATE		REV NO	
CHECKED BY		SIGN		DATE		DESCRIPTION	
APPROVED BY		SIGN		DATE		SO NO:	

MATERIAL :- AS PER BOM		PROJECT NAME & NO:		SHEET NO: 01 OF 01	
ENQ NO: EN222300744		SO NO:		REV NO: 00	
* All dimensions are in mm. Dimensions for reference only and are subject to change without notice		* This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI.		SCALE: NTS	

PATH: X:\2022-2023\EXPORT\EN222300744