


SR.	DESCRIPTION	MATERIAL	QTY
1	HANDLE	NYLON	1
2	BODY	ASTM A182 Gr.F316	1
3	PUSHER	ASTM A479 Gr. SS316	1
4	PACKING	PTFE	1
5	SPINDLE	ASTM A479 Gr. SS316	1
6	SEAL RING	PTFE	3
7	BALL	ASTM A479 Gr. SS316	1
8	END CONNECTOR	ASTM A479 Gr. SS316	3
9	SEAT	PEEK	2
10	THRUST WASHER	PTFE	1
11	PANNEL NUT	SS304	1
12	GRUB SCREW	SS304	1

DATA SHEET

Type : 3 Way 'L' Port
 Connection : 1/4" NPT(F)
 Orifice: 6mm

Working Press : 6000 psig
 Seat Test (Hydro) : 6600 psig
 Body Test (Hydro) : 9000 psig
 Pneumatic Seat Test : 90 psig
 Temp. Range:- -54 to 260°C

 Fittings & Valves info@havi.in www.havi.in A-201, PRIME TRADE CENTER SATIVALI ROAD, VASAI (E), PALGHAR - 401208, MAHARASHTRA, INDIA		PART NAME : Medium Pressure Ball Valve 3 way, 1/4" NPT-F				CUSTOMER NAME: -			
		DWG NO : MBV-4F3W-S6				PROJECT NAME & NO: -			
		MATERIAL : AS PER BOM				ENQ NO: EN2223/00927			
						SO NO: -			
DRAWN BY		SB	11.11.2022	REV NO	DESCRIPTION	SIGN	DATE	SHEET NO: 01 OF 01	
CHECKED BY		VK	11.11.2022	* All dimensions are in mm. Dimensions for reference only and are subject to change without notice				REV NO: 00	
APPROVED BY		SM	11.11.2022	* This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI.				SCALE: NTS	