

13

12

11

10

SR.	DESCRIPTION	MATERIAL	QTY
1	HANDLE	NYLON 6	1
2	GRUB SCREW	SS316	1
3	SPINDLE	ASTM A479 Gr.SS316	1
4	PUSHER	SS316	1
5	LOCK NUT	SS316	1
6	PACKING	PTFE	2
7	END CONNECTOR	ASTM A479 Gr.SS316	2
8	CONNECTOR PACKING	PTFE	2
9	BALL SEAT	PEEK	2
10	BODY	ASTM A479 Gr.SS316	1
11	BALL	ASTM A479 Gr.SS316	1

**CUSTOMER NAME:** 

 $\oplus \Box$ 

SHEET NO: 01 OF 01

REV NO: 00

SCALE: NTS

## **DATA SHEET**

Type: 2 Way, Full Port

Inlet Connection: 1/2" NPT(F) Outlet Connection: 1/2" NPT(F)

Orifice: 10.3mm

16

Working Press: 6000 psi Seat Test (Hydro): 6600 psi Body Test (Hydro): 9000 psi Pneumatic Seat Test: 90 psi

15

<b>         </b>	-	,i	PART NAME: Medium Pressure Panel Mounted Ball Valve, 1/2" NPT-F & 1/2" NPT-F				CUSTOMER NAME:		
			DWG NO : - MBV-8F-8F-86 MATERIAL : - AS PER BOM				PROJECT NAME :		
Fittings & Valves									
info@havi.in www.havi.in A-201. PRIME TRADE CENTER							ENQ NO: EN2324/00354		
SATIVALI ROAD, VASAI (E), PALGHAR - 401208, MAHARASHTRA, INDIA							2.10.10.2.1202.70000		
							SO NO:		
	SIGN	DATE	REV NO	DESCRIPTION	SIGN	DATE	30 110.		
DRAWN BY	MBC	04.07.2023	* All dimensions are in mm. Dimensions for reference only and are subject to change without notice						
CHECKED BY	MV	04.07.2023	* This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text						
APPROVED BY	SD	04.07.2023	contained herein or relating to this document is permitted in any form without the written consent of HAVI.						