



SR.	DESCRIPTION	MATERIAL	QTY
1	HANDLE	SS 304	1
2	BODY	ASTM A479 Gr.316	1
3	PUSHER	ASTM A479 Gr.316	1
4	PACKING	PTFE	1
5	SPINDLE	ASTM A479 Gr.316	1
6	SEAL RING	PTFE	2
7	BALL	ASTM A479 Gr.316	1
8	END CONNECTOR	ASTM A479 Gr.316	2
9	SEAT	PEEK	2
10	THRUST WASHER	PTFE	1
11	PANEL NUT	SS316	1
12	LOCKER	SS316	1
13	HANDLE NUT	SS316	1



DATA SHEET

Type : 3 Way 'L' Port
 Connection : 1/2" BSPT(F)
 Orifice: 10.3mm

M.W.T:- -54°C To 260°C
 Working Press : 6000 psi
 Seat Test (Hydro) : 6600 psi
 Body Test (Hydro) : 9000 psi
 Pneumatic Seat Test : 90 psi

havi
 Fittings & Valves
 info@havi.in www.havi.in
 A-201, PRIME TRADE CENTER
 SATIVALI ROAD, VASAI (E),
 PALGHAR - 401208, MAHARASHTRA, INDIA

SIGN	DATE
DRAWN BY	MBC 17.07.2023
CHECKED BY	VM 17.07.2023
APPROVED BY	SRD 17.07.2023

PART NAME : Medium Pressure Ball Valve 3 way, 1/2" BSPT-F		CUSTOMER NAME: -	
DWG NO : - MLBV-8ITF3W-S6		PROJECT NAME & NO:	
MATERIAL : - AS PER BOM		ENQ NO: 2324/00424	
R1 Update Temperature Range		MBC 21.07.2023	SO NO: NA
REV NO	DESCRIPTION	SIGN	DATE
* All dimensions are in mm. Dimensions for reference only and are subject to change without notice			SHEET NO: 01 OF 01
* This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI.			REV NO: 00
			SCALE: NTS

PATH: X:\2023-2024\EXPORT\232400424\GAD 232400424\R1-21.07.2023