

SR NO	MODEL NO.	Tx	F(A/F)	L	Qty
34	12NMP	3/4" NPT-M	27.0(1/1-16")	27.0	11
35	16NMP	1" NPT-M	36.0(1-7/16")	34.0	11

NOTES:-

16

| 1)ALL DIMENSIONS ARE IN MM UNLESS AND OTHERWISE SPECIFIED.

13

12

2) # MARKED DIMENSIONS ARE IN FINGER TIGHT POSITION. 3)THREAD CONNECTIONS AS PER ANSI/ASME B1.20.1 (NPT)

 \pm 4)TEMPERATURE RANGE - -192°C TO 649°C.

[5] 5 MWP.: 3000 PSIG @ 100 °F 15

			MATERIAL : SS 316					DO NO. 1/0D 44044704			
		SIGN	DATE						O NO:- VSP-140	41794	
	DRAWN BY	PDG	22-08-2023					F	NQ NO: EN2223	1/01219	
[CHECKED BY	VSM	22-08-2023						ING NO. LINZZZO	701210	
[APPROVED BY	SRD	22-08-2023								
				REV NO	DESCR	IPTION	SIGN	DATE	SO NO:- SO2324/00159		
	Fittings & V	www.havi.in info@havi.in	* All dimensions are in mm. Dimensions for reference only and are subject to change without notice * This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI								
11) (a	Q		7	6		5	1	3	$\overline{}$

CUSTOMER NAME:-

PROJECT NAME:-

SHEET NO: 17 OF 20

REV NO: 00

SCALE: NTS

PART NAME: MALE PLUG

DWG NO : GA-NMP-S6