

SR NO	PART DESCRIPTION	MATERIAL	QTY
1	BODY	ASTM Gr.A105	1
2	TIP	ASTM A479 Gr.SS316	1
3	BONNET WASHER	ASTM A479 Gr.SS316	1
4	GLAND PACKING	GRAPHITE	1
5	BACKUP WASHER	ASTM A479 Gr.SS316	1
6	BONNET PUSHER	ASTM Gr.A105	1
7	HANDLE	SS304	1
8	GRUB SCREW	SS304	2
9	SPINDLE	ASTM A479 Gr.SS316	1
10	CHECK NUT	SS304	1
11	BONNET	ASTM Gr.A105	1
12	DOWEL PIN	SS304	1
13	DUST CAP	ALUMINIUM	1

Process Conn.
3/4" BSPT(F)

Instrument Conn.
3/4" BSPT(F)

65 ±2.0



Approx 100 (Open)

Data Sheet.
 Process Conn.: 3/4" BSPT(F)
 Instrument Conn.: 3/4" BSPT(F)

 Orifice.: 4mm

 Screwed Bonnet Design

 Temperature Range : -20°F To 800°F
 M W P.: 6000 psig @ 100 °F
 Seat Test Press (Hydro): 6600 psig
 Seat Test Press (Pneu): 90 psig
 Body Test Press (Hydro): 9000 psig

 Fittings & Valves info@havi.in www.havi.in A-201, PRIME TRADE CENTER SATIVALI ROAD, VASAI (E), PALGHAR - 401208, MAHARASHTRA, INDIA	PART NAME : BAR STOCK NEEDLE VALVE, 3/4"BSPT FEMALE X 3/4"BSPT FEMALE				CUSTOMER NAME :										
	DWG NO : - NVBS-12ITF-12ITF-A105-G				PROJECT NAME :										
	MATERIAL : - AS PER BOM				ENQ NO : - 2300-000329										
	REV NO				DESCRIPTION				SIGN				DATE		
DRAWN BY				MC				30-06-2023				* All dimensions are in mm. Dimensions for reference only and are subject to change without notice			
CHECKED BY				MT				30-06-2023				* This document is the property of Havi Engineering India Pvt. Ltd. No exploitation or release of any text contained herein or relating to this document is permitted in any form without the written consent of HAVI.			
APPROVED BY				SRD				30-06-2023				SO NO :-			
												 SHEET NO: 01 OF 01			
												REV NO: 00			
												SCALE: NTS			

PATH: C:\USERS\DESIGN\2\DESKTOP\ENQUIRY\2300-000329