


Sr No.	Description	Material	Qty
1	Tip	ASTM A479 Gr. SS316L	3
2	Bonnet Packing	ASTM A479 Gr. SS316L	3
3	Gland Packing	GFT	3 Set
4	Gland Washer	ASTM A479 Gr. SS316L	3
5	Bonnet Pusher	ASTM A479 Gr. SS316L	3
6	Handle	SS 304	3
7	Grub Screw	SS 304	6
8	Spindle	ASTM A479 Gr. SS316L	3
9	Drain Cap	PVC	3
10	Check Nut	SS304	3
11	Bonnet	ASTM A479 Gr. SS316L	3
12	Dowel Pin	SS304	3
13	Body	ASTM A182 Gr. SS316L	1
14	Male Plug	ASTM A479 Gr. SS316L	2

**TECHNICAL DETAILS:**

- Process Side: 1/2" NPT-F
- Instrument Side: Direct Mount Flg
- Test Port: 1/4" NPT-F
- Screwed Bonnet Design
- MWP : 6000 psig @100°F
- Seat Test Press (Hydro): 6600 psig
- Seat Test Press (Pneu): 90 psig
- Body Test Press (Hydro) : 9000 psig



**havi**  
Fittings & Valves  
info@havi.in www.havi.in  
A-201, PRIME TRADE CENTER  
SATIALI ROAD, VASAI (E),  
PALGHAR - 401208, MAHARASHTRA, INDIA

	SIGN	DATE
DRAWN BY	SB	12.01.2023
CHECKED BY	RW	12.01.2023
APPROVED BY	SD	12.01.2023

PART NAME : 3 WAY MANIFOLD VALVE-1/2" NPT-F x FLANGE x 1/4" NPT-F TEST PORT		CUSTOMER NAME:	
DWG NO : - TV3C-8F-4TP-S6L		PROJECT NAME & NO:	
MATERIAL :- AS PER BOM		ENQ NO:EN2223/01146	
REV NO	DESCRIPTION	SIGN	DATE

SO NO: -	SHEET NO: 01 OF 01
	REV NO: 00
	SCALE: NTS

PATH: Z:\2022-2023\EXPORT\EN222301146\GAD